

eNBioAccess-T1

Entry Level Fingerprint / Card Access Terminal



Features



- Bluetooth Support**
- Bluetooth-enabled Mobile Card Solution
 - Terminal Menu Control in Mobile Phone (iAccess M Plus)
 - Mobile Card Authentication (NITGEN Mobile Card)



- IP65 Rated Weatherproof**
- Water and Dust Resistance



- Fake Finger Detection**
- Optical sensor and algorithm detect fake fingers (Paper, Film, Silicone, Rubber and Gelatin)



- Terminal Status Indicator**
- 3 Color LED Indicator
 - Beep & Voice Sound Indicator

※ Real-Time Door Access Monitoring

Specification

CPU	ATMEL 400MHz	Log Capacity	100,000 (logs)
Memory	64MB DRAM / 256MB Flash	Communication	RS-485, Wiegand Out, TCP/IP
Sensor	Optical / 500DPI	Supported Card	EM, HID, iClass(Optional), Mifare
Authenticaiton Type	Fingerprint, RF Card	Lock	Deadbolt, EM Lock, Door Strike, Automatic Door
TIME	1:1	< 0.2 Sec	Environment
	1:N	< 1 Sec (4,000 Templates)	
Template Capacity	20,000 Templates	Certificate	KC, CE, FCC
		Dimensions	58(W) x 188(H) x 49.8(D) mm

